

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently Amended) A method of manufacturing a plasma display device having a panel in which a pair of substrates having transparency at least on a front side, the substrates being oppositely disposed so that a discharge space and discharge cells are formed between the substrates, and a metallic holding plate that supports the panel via a thermal conductive material, the method comprising:

forming the thermal conductive material ~~from a of a~~ pull-to-remove type adhesive;

applying the adhesive to one of the panel and the holding plate, and applying heat and pressure to the panel and the holding plate for forming a bulging-out portion of the adhesive bulging out from between the panel and the plate;

~~bonding the panel to the holding plate together; and~~

curing the adhesive ~~by simultaneous application of pressure and heat; for bonding the panel and the holding plate together;~~

~~wherein a groove in which a portion of the adhesive flows and is formed at a periphery of the holding plate, the groove accepting the portion of the flowed adhesive and preventing it from leaking to the outside of the holding plate forming a groove around the holding plate for a portion of the adhesive to flow into the groove so that the portion of the adhesive can be prevented from hanging out outside the holding plate.~~

2. - 12. (Cancelled)

13. (Original) The method of manufacturing the plasma display device of Claim 1, wherein a driving circuit block containing a semiconductor device for feeding a display signal to the panel is mounted on a cooling plate on a back side of the holding plate, a portion of the thermal conductive material is exposed from the holding plate, and the driving circuit block-mounted cooling plate is bonded with the exposed portion of the thermal conductive material.

14. (Original) The method of manufacturing the plasma display device of Claim 1, wherein a driving circuit block containing a semiconductor device for feeding a display signal to the panel is mounted on a cooling plate on a back side of the holding plate, a portion of the thermal conductive material is extended to the driving circuit block-mounted cooling plate.

15. - 18. (Cancelled)

19. (New) The method of manufacturing the plasma display device of Claim 1, further comprising pulling the bulging-out portion to allow the panel to be removed from the holding plate.